

**SOFT PLASTICS CLEAR GLUE**  
**Supersedes Date:** 14-May-2020

**Revision date** 14-May-2020  
**Revision Number** 1.03

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product Identifier

**Product Name** SOFT PLASTICS CLEAR GLUE  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Adhesive.  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
 Common Rd  
 ST16 3EH  
 Stafford UK  
 Tel: +44 (1785) 27 26 25  
 Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650  
**Ireland** +353 (1) 8624900 (Monday- Friday 9am-5pm)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

<b>Serious eye damage/eye irritation</b>	Category 2 - (H319)
<b>Skin sensitisation</b>	Category 1 - (H317)
<b>Specific target organ toxicity (single exposure)</b>	Category 3 - (H336)
<b>Chronic aquatic toxicity</b>	Category 3 - (H412)
<b>Flammable liquids</b>	Category 2 - (H225)

### 2.2. Label Elements

Contains: Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Acetone, Methyl ethyl ketone, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics



**Signal word**  
 DANGER

#### Hazard statements

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supersedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

H319 - Causes serious eye irritation.  
H412 - Harmful to aquatic life with long lasting effects.  
H336 - May cause drowsiness or dizziness.  
H317 - May cause an allergic skin reaction.  
H225 - Highly flammable liquid and vapour.

## EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking.  
EUH205 - Contains epoxy constituents. May produce an allergic reaction.

## Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves and eye/face protection.  
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a POISON CENTER or doctor if you feel unwell.  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
P235 - Keep cool.  
P501 - Dispose of contents/ container to an approved waste disposal plant.

## Additional information

This product requires tactile warnings if supplied to the general public.

## 2.3. Other Hazards

In use may form flammable/explosive vapour-air mixture

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Mixture

### 3.2. Mixtures 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Acetone	200-662-2	67-64-1	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119471330-49-XXXX
Methyl ethyl ketone	201-159-0	78-93-3	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119457290-43-XXXX

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supersedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	--	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) (EUH066)		01-2119473851-33-XXXX
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	500-033-5	25068-38-6	1 - <5	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	01-2119456619-26-xxxx

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Call a doctor or poison control centre immediately.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Itching. Rashes. Hives. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	--

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

## SECTION 5: Firefighting measures

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supercedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

## 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray. Alcohol resistant foam.
<b>Unsuitable extinguishing media</b>	Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient.

## 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitiser. May cause sensitisation by skin contact.
<b>Hazardous combustion products</b>	Carbon oxides.

## 5.3. Advice for firefighters

<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Keep people away from and upwind of spill/leak.
<b>Other information</b>	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
<b>For emergency responders</b>	Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.
----------------------------------	--

### 6.3. Methods and material for containment and cleaning up

<b>Methods for containment</b>	Dyke far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
<b>Methods for cleaning up</b>	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. Take up mechanically, placing in appropriate containers for disposal.
<b>Prevention of secondary hazards</b>	Eliminate all ignition sources if safe to do so.

### 6.4. Reference to other sections

<b>Reference to other sections</b>	See section 8 for more information. See section 13 for more information.
------------------------------------	--

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

<b>Advice on safe handling</b>	Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other
--------------------------------	---

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supersedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

**General hygiene considerations** Keep away from food, drink and animal feedingstuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store locked up. Keep out of the reach of children.

## 7.3. Specific end use(s)

**Specific Use(s)**  
Adhesive.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup>	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup> STEL: 1500 ppm STEL: 3630 mg/m <sup>3</sup>	TWA: 500 ppm TWA: 1210 mg/m <sup>3</sup> STEL: 1500 ppm STEL: 3620 mg/m <sup>3</sup>
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m <sup>3</sup> STEL: 300 ppm STEL: 900 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 600 mg/m <sup>3</sup> STEL: 300 ppm STEL: 900 mg/m <sup>3</sup> Sk*	TWA: 200 ppm TWA: 600 mg/m <sup>3</sup> STEL: 300 ppm STEL: 899 mg/m <sup>3</sup> Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl ethyl ketone 78-93-3	-	-	70 µmol/L urine

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects	Inhalation	2420 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
 Supersedes Date: 14-May-2020

Revision date 14-May-2020  
 Revision Number 1.03

worker			
Long term Systemic health effects worker	Inhalation	1210 mg/m <sup>3</sup>	

Methyl ethyl ketone (78-93-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	1161 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	600 mg/m <sup>3</sup>	

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d	

Derived No Effect Level (DNEL) Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

Methyl ethyl ketone (78-93-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	106 mg/m <sup>3</sup>	
Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d	

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

**Predicted No Effect Concentration (PNEC)**

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supercedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

<b>Acetone (67-64-1)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

<b>Methyl ethyl ketone (78-93-3)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

<b>Bisphenol-A-Epichlorhydrin Epoxy resin &lt;= 700 MW (25068-38-6)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.0006 mg/l
Freshwater sediment	0.996 mg/l
Marine sediment	0.0996 mg/l
Soil	0.196 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

### Personal Protective Equipment

**Eye/face protection** Tight sealing safety goggles. Face protection shield.  
**Hand protection** Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.  
**Skin and body protection** Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.  
**Respiratory protection** In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. In case of inadequate ventilation wear respiratory protection.  
**Recommended filter type:** Organic gases and vapours filter conforming to EN 14387.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** Liquid  
**Appearance** Paste  
**Colour** Clear  
**Odour** Characteristic  
**Odour threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	56 °C	
Flash point	-20 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supersedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

---

<b>Lower flammability or explosive limits</b>	No data available
<b>Vapour pressure</b>	No data available
<b>Vapour density</b>	No data available
<b>Relative density</b>	0.87
<b>Water solubility</b>	No data available
<b>Solubility(ies)</b>	No data available
<b>Partition coefficient</b>	No data available
<b>Autoignition temperature</b>	No data available
<b>Decomposition temperature</b>	No data available
<b>Kinematic viscosity</b>	approx. 4950 mm <sup>2</sup> /s @ 20 °C
<b>Dynamic viscosity</b>	No data available
<b>Explosive properties</b>	No data available
<b>Oxidising properties</b>	No data available

## 9.2. Other information

<b>Solid content (%)</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Density</b>	No information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** No information available.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

#### **Explosion Data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** Yes.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Heat, flames and sparks.

### 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### **Product Information**

**Inhalation** May cause irritation of respiratory tract. May cause drowsiness or dizziness.



# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supersedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

<b>Eye contact</b>	Causes serious eye irritation. May cause redness, itching, and pain.
<b>Skin contact</b>	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause irritation. Prolonged contact may cause redness and irritation.
<b>Ingestion</b>	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Itching. Rashes. Hives. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## Numerical measures of toxicity

### Acute Toxicity

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Methyl ethyl ketone 78-93-3	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	May cause skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitisation</b>	May cause sensitisation by skin contact.
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.
<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.
<b>STOT - single exposure</b>	May cause drowsiness or dizziness.
<b>STOT - repeated exposure</b>	Based on available data, the classification criteria are not met.
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supersedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor	M-Factor (long-term)
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)		
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphia Magna		

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

### 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

#### Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Acetone 67-64-1	-0.24	0.69
Methyl ethyl ketone 78-93-3	0.3	-
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	3.26	31

### 12.4. Mobility in soil

**Mobility in soil** No information available.

### 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** No information available.

Chemical name	PBT and vPvB assessment
Acetone	The substance is not PBT / vPvB

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supersedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

67-64-1	
Methyl ethyl ketone 78-93-3	The substance is not PBT / vPvB
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	The substance is not PBT / vPvB

## 12.6. Other adverse effects

Other adverse effects No information available.

## Endocrine Disruptor Information

Chemical name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	Group III Chemical	-

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
<b>Contaminated packaging</b>	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
<b>European Waste Catalogue</b>	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

### Land transport (ADR/RID)

<b>14.1 UN Number</b>	UN1133
<b>14.2 Proper Shipping Name</b>	Adhesives
<b>14.3 Transport hazard class(es)</b>	3
<b>Labels</b>	3
<b>14.4 Packing Group</b>	II
<b>Description</b>	UN1133, Adhesives, 3, II, (D/E)
<b>14.5 Environmental hazards</b>	Not applicable
<b>14.6 Special Provisions</b>	640C
<b>Classification Code</b>	F1
<b>Tunnel restriction code</b>	(D/E)
<b>Limited Quantity (LQ)</b>	5 L
<b>ADR Hazard Id (Kemmler Number)</b>	33

### IMDG

<b>14.1 UN number</b>	UN1133
<b>14.2 Proper Shipping Name</b>	Adhesives
<b>14.3 Transport hazard class(es)</b>	3
<b>14.4 Packing group</b>	II
<b>Description</b>	UN1133, Adhesives, 3, II, (-20°C c.c.)

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supersedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

---

14.5 Marine Pollutant	Np
14.6 Special Provisions	None
Limited Quantity (LQ)	5 L
EmS-No.	F-E, S-D
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	UN1133
14.2 Proper Shipping Name	Adhesives
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1133, Adhesives, 3, II
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A3
Limited Quantity (LQ)	1 L
ERG Code	3L

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Dangerous substance category per Seveso Directive (2012/18/EU)**

P5a - FLAMMABLE LIQUIDS  
or  
P5b - FLAMMABLE LIQUIDS  
or  
P5c - FLAMMABLE LIQUIDS

##### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

# SAFETY DATA SHEET

SOFT PLASTICS CLEAR GLUE  
Supersedes Date: 14-May-2020

Revision date 14-May-2020  
Revision Number 1.03

## National Regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking  
H225 - Highly flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

#### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

#### **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 14-May-2020

#### Indication of changes

**Revision note** Not applicable.

**Training Advice** Provide adequate information, instruction, and training for operator

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**