



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 13

LOCTITE LB 8065 known as Loctite 8065

SDS No. : 153550  
V006.0

Revision: 26.05.2021  
printing date: 27.05.2021

Replaces version from: 04.01.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE LB 8065 known as Loctite 8065

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:  
Lubricant

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd  
Adhesives  
Wood Lane End  
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000  
Fax-no.: +44 (1442) 278071

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

||| Chronic hazards to the aquatic environment Category 3  
||| H412 Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements (CLP):

||| Hazard statement: H412 Harmful to aquatic life with long lasting effects.

||| Precautionary statement: P273 Avoid release to the environment.  
Prevention

**2.3. Other hazards**

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****General chemical description:**

Lubricant

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Copper 7440-50-8	231-159-6 01-2119480154-42	10- 20 %	Aquatic Acute 1 H400 Aquatic Chronic 2 H411
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	265-156-6 01-2119480375-34	10- 20 %	Asp. Tox. 1 H304

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

**SECTION 4: First aid measures****4.1. Description of first aid measures**

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Prolonged or repeated contact may cause eye irritation.

Prolonged or repeated contact may cause skin irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media:**

water, carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Wear protective equipment.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

Dispose of contaminated material as waste according to Section 13.

Scrape up as much material as possible.

Sweep up spilled material. Avoid creating dust.

Store in a partly filled, closed container until disposal.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Ensure good ventilation/extraction.

Store in a cool, well-ventilated place.

Keep away from heat and direct sunlight.

Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Lubricant

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational Exposure Limits

Valid for  
Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Copper 7440-50-8 [COPPER, FUME]		0,2	Time Weighted Average (TWA):		EH40 WEL
Copper 7440-50-8 [COPPER, INHALABLE DUSTS AND MISTS (AS CU)]		1	Time Weighted Average (TWA):		EH40 WEL
Copper 7440-50-8 [COPPER, INHALABLE DUSTS AND MISTS (AS CU)]		2	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Graphite 7782-42-5 [GRAPHITE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Graphite 7782-42-5 [GRAPHITE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL

#### Occupational Exposure Limits

Valid for  
Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Copper 7440-50-8 [COPPER]		0,2	Time Weighted Average (TWA):		IR_OEL
Copper 7440-50-8 [COPPER]		1	Time Weighted Average (TWA):		IR_OEL
Graphite 7782-42-5 [GRAPHITE (ALL FORMS EXCEPT FIBRES) (RESPIRABLE FRACTION)]		2	Time Weighted Average (TWA):		IR_OEL
Graphite 7782-42-5 [GRAPHITE (ALL FORMS EXCEPT FIBRES)]		2	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 [MINERAL OIL PURE, HIGHLY & SEVERELY REFINED]		5	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]				Included in the regulation but with no data values. See regulation for further details	IR_OEL
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO			Skin designation:	Can be absorbed through the skin.	IR_OEL

64742-53-6 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]					
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6 [MINERAL OIL PURE, HIGHLY & SEVERELY REFINED]		5	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]				Included in the regulation but with no data values. See regulation for further details	IR_OEL

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Copper 7440-50-8	Soil				65 mg/kg		
Copper 7440-50-8	sewage treatment plant (STP)		230 µg/l				
Copper 7440-50-8	sediment (marine water)				676 mg/kg		
Copper 7440-50-8	aqua (freshwater)		7,8 µg/l				
Copper 7440-50-8	aqua (marine water)		5,2 µg/l				
Copper 7440-50-8	sediment (freshwater)				87 mg/kg		
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	oral				9,33 mg/kg		

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Copper 7440-50-8	Workers	dermal	Acute/short term exposure - systemic effects		273 mg/kg	
Copper 7440-50-8	General population	inhalation	Acute/short term exposure - local effects		1 mg/m3	
Copper 7440-50-8	General population	inhalation	Long term exposure - local effects		1 mg/m3	
Copper 7440-50-8	General population	dermal	Acute/short term exposure - systemic effects		273 mg/kg	
Copper 7440-50-8	Workers	dermal	Long term exposure - systemic effects		137 mg/kg	
Copper 7440-50-8	General population	dermal	Long term exposure - systemic effects		137 mg/kg	
Copper 7440-50-8	General population	oral	Long term exposure - systemic effects		0,041 mg/kg	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:  
Ensure good ventilation/extraction.

Respiratory protection:  
Ensure adequate ventilation.  
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area  
Filter type: A (EN 14387)

Hand protection:  
Chemical-resistant protective gloves (EN 374).  
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):  
nitrile rubber (NBR;  $\geq 0.4$  mm thickness)  
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):  
nitrile rubber (NBR;  $\geq 0.4$  mm thickness)  
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:  
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.  
Protective eye equipment should conform to EN166.

Skin protection:  
Wear suitable protective clothing.  
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	solid
	light brown
Odor	mild
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	No data available / Not applicable
Flash point	Product is a solid. Burn Rate: Approx 14 mm/2 minutes
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density	1,18 g/cm <sup>3</sup>
( )	
Bulk density	No data available / Not applicable

Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

**9.2. Other information**

No data available / Not applicable

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Reacts with strong oxidants.

**10.2. Chemical stability**

Stable under recommended storage conditions.

**10.3. Possibility of hazardous reactions**

See section reactivity

**10.4. Conditions to avoid**

Stable under normal conditions of storage and use.

**10.5. Incompatible materials**

See section reactivity.

**10.6. Hazardous decomposition products**

Irritating organic vapours.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Copper 7440-50-8	LD50	> 2.500 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Copper 7440-50-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Copper 7440-50-8	LC50	> 5,11 mg/l	dust/mist	4 h	rat	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method)
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	LC50	> 5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Copper 7440-50-8	not irritating		rabbit	EU Method B.4 (Acute Toxicity: Dermal Irritation / Corrosion)

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Copper 7440-50-8	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Copper 7440-50-8	not sensitising	Guinea pig maximisation test	guinea pig	EU Method B.6 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Copper 7440-50-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Copper 7440-50-8	negative	oral: gavage		mouse	EU Method B.12 (Mutagenicity)
Copper 7440-50-8	negative	oral: gavage		rat	equivalent or similar to OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)

**Carcinogenicity**

No data available.



**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Copper 7440-50-8	NOAEL P 1500 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm	two- generation study	oral: feed	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Copper 7440-50-8	NOAEL P 1000 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm	two- generation study	oral: feed	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure::**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Copper 7440-50-8	NOAEL 1000 ppm	oral: feed	92 d 7 d/w	rat	EU Method B.26 (Sub- Chronic Oral Toxicity Test: Repeated Dose 90- Day Oral Toxicity Study in Rodents)

**Aspiration hazard:**

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	9 mm <sup>2</sup> /s	40 °C	not specified	

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Copper 7440-50-8	LC50	0,193 mg/l	96 h	Pimephales promelas	other guideline:
Copper 7440-50-8	NOEC	0,188 mg/l	30 d	Perca fluviatilis	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	LL50	> 100 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Copper 7440-50-8	EC50	> 0,1 - 1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Copper 7440-50-8	NOEC	> 0,1 - 1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	NOEL	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Copper 7440-50-8	EC50	> 0,1 - 1 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Copper 7440-50-8	NOEC	> 0,1 - 1 mg/l	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Copper 7440-50-8	EC50	> 0,1 - 1 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Copper 7440-50-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Distillates (petroleum), hydrotreated light naphthenic < 3% DMSO 64742-53-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

#### 12.6. Other adverse effects

No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

**SECTION 14: Transport information****14.1. UN number**

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	3077
IATA	Not dangerous goods

**14.2. UN proper shipping name**

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Copper)
IATA	Not dangerous goods

**14.3. Transport hazard class(es)**

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	9
IATA	Not dangerous goods

**14.4. Packing group**

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	III
IATA	Not dangerous goods

**14.5. Environmental hazards**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	No dangerous good according to ADR/RID/ADN. Carriage in accordance with 1.1.4.2.1 ADR/RID/ADN.
IATA	not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

**EU. REACH, Annex XVII, Marketing and Use Restrictions (Regulation 1907/2006/EC):** Not applicable

VOC content < 3 %  
(2010/75/EC)

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H304 May be fatal if swallowed and enters airways.  
H400 Very toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**