

Safety CAT III 600V

Featue	Range & Resolution
Insulation resistance with 250, 500& 1000VDC test voltages	0- 4.000/40.00/400.0/ 4000MΩ
Low resistance	0- 400.0, 4000Ω
AC/DC Voltage	0.1 - 600.0V

Replacement Parts (supplied with product)	Part Number
Carrying case	GP-2CC
Special download cable	RS-JACK
test leads complete set	MTL-45
Instruction Manual	www.amprobe.com



AMPROBE[®] AMB-45 MegaTest 1 Digital Megohmmeter – Insulation Resistance Tester

GENERAL SPECIFICATION:

• Display:

70 x 46mm LCD with 60 segment analog bar Indicator.

- Over range Indication:
 - "OL" will be shown on the LCD Panel when an out of range measurement is made.
- Low Battery Indication:
- The symbol is displayed indicating a low battery condition.
- Sampling Rate:
- 2.5 times/sec Digital Display; 10 times/sec Bar Graph
- Power Source:
- 1.5V AA size Battery X 8
- Operating Temperature and Humidity: 0°C to 40°C (32°F to 104°F), below 80% RH
- Storage Temperature:
- -10°C to 60°C (14°Fto 140°F)
- Dimension:

230 x 116 x 62 mm ; 9 x 4.6 x 2.4 inch

- Weight:
- Approx. 750g(with battery)
- Accessories:

Test Lead, Large Jaw Alligator Clips, Batteries, Instruction Manual, Carrying Case, software, RS-232 cable.

III. ELECTRICAL SPECIFICATION:

AC Voltage

Range	Resolution	Accuracy
600V	0.1V	1.5%rdg+5dgts

DC Voltage

Range	Resolution	Accuracy
600V	0.1V	1%rdg+3dgts

Ohms (Autoranging)

Range	Resolution	Accuracy
400Ω 4000Ω	0.1Ω 1Ω	1%rdg+5dgts

Continuity beeper

Range	Resolution	Protection
•3))	40Ω	250Vms

$M\Omega$ (Autoranging)

Range	Resolution	Accuracy
4/40/400/400M_(250V) 4/40/400/4000M_(500V) 4/40/400/400M_(1000V)	1ΚΩ	3%rdg+5dgts < 2GΩ 5%rdg+5dgts < 4GΩ

Recording Length: 4000 records

Safety: N-61010-1 600V CAT III 1000V CATII VDE 0413



www.Amprobe.com