



## Section 1. Product and Company Identification.

**1.1 Model Number;** SCS034 v1  
**1.2 Description;** Grey Zinc Primer Paint 500ml Pack of 6

**1.3 Manufacturer;**

Sealey Group.  
Kempson Way,  
Bury St. Edmunds,  
Suffolk.  
IP32 7AR

**1.4 Emergency telephone number;** 44 (0) 1284 757 500 (Office Hours)

**Date of source compilation;** 30 November 2015

## Section 2. Hazards Identification.

**2.1 Classification of the substance or mixture.**

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Aerosol 1 - H222
Human health	EUH066
Environment	Not classified.

Classification (1999/45/EEC) Xn; R20/21. Xi; R36/38. F+; R12.

**Risk phrases;**

R12 Extremely flammable.  
R10 Flammable.  
R20/21 Harmful by inhalation and in contact with skin.  
R11 Highly flammable  
R36/38 Irritating to eyes and skin.  
R36 Irritating to eyes.  
R38 Irritating to skin.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

**Section 2. Hazards Identification (continued).**

**2.2 Label elements.**

**Hazard pictogram(s)**



**Signal Word.**

Danger

**Hazard statements;**

- H222 Extremely flammable aerosol.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements;**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P102 Keep out of reach of children.
- P271 Use only outdoors or in a well-ventilated area.
- P261 Avoid breathing vapour/spray.
- P280 Wear protective clothing and gloves.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+313 If eye irritation persists: Get medical advice/attention.
- P501 Dispose of contents/container in accordance with local regulations.

**Supplementary Precautionary Statements**

- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P264 Wash contaminated skin thoroughly after handling.
- P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

**Supplementary label information**

- H280 Contains gas under pressure: May explode if heated.
- EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards.**

No information available.



### Section 3. Substances.

3.1 Chemical Name (substance)	3.1 CAS No.	3.2 Concentration Volume	Classification	
			Hazard Class & Category Code	Hazard Statements
Dimethyl Ether	115-10-6	30-60%	Flam. Gas 1 Press. Gas	H220
Acetone	67-64-1	10-30%	Eye Irrit. 2 STOT SE 3	H319 H336
Xylene	1330-20-7	10-30-%	Flam. Liq. 3 Acute Tox. 4 Skin Irrit. 2 Asp. Tox. 1	H226 H312 H315 H304
Zinc Dust	7440-66-6	10-30%	Aquatic Acute 1 Aquatic Chronic 1	H400 H410
1-Methoxy-2-Propanol	107-98-2	1-5%	Flam. Liq. 3 STOT SE 3	H226 H336
Butane	106-97-8	1-5%	Flam. Gas 1 Press. Gas	H220
Butyl Acetate –norm	123-86-4	1-5%	Flam. Liq. 3 STOT SE 3	H226 H336
Propane	74-98-6	1-5%	Flam. Gas 1 Press. Gas	H220
Isobutane	75-28-5	<1%	Flam. Gas 1 Press. Gas	H220

For full text of Phrases and Statements, see Section 16.



## Section 4. First Aid Measures.

### General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

#### 4.1 Description of first aid measures

##### **Eye Contact**

Make sure to remove any contact lenses from the eyes before rinsing.

Promptly wash eyes with plenty of water while lifting the eye lids.

Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

##### **Skin Contact**

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

##### **Ingestion**

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water, ensure that casualty is fully conscious before doing this. Get medical attention if any discomfort continues.

##### **Inhalation**

Move the exposed person to fresh air at once.

Keep the affected person warm and at rest. Get prompt medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## Section 5. Fire Fighting Measures.

#### 5.1. Extinguishing media

Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### 5.2. Special hazards arising from the substance or mixture

Aerosol cans may explode in a fire.

#### 5.3. Advice for fire-fighters

Containers close to fire should be removed or cooled with water.

Use water to keep fire exposed containers cool and disperse vapours.



## Section 6. Accidental Release Measures.

**6.1.** Personal precautions, protective equipment and emergency procedures  
No information available.

**6.2.** Environmental precautions  
No information available.

**6.3.** Methods and material for containment and cleaning up  
Wear necessary protective equipment. Extinguish all ignition sources.  
Avoid sparks, flames, heat and smoking.  
Ventilate.  
Let evaporate.  
Keep out of confined spaces because of explosion risk.  
If leakage cannot be stopped, evacuate area.

**6.4.** Reference to other sections  
See Section 7 for information on Safe Handling  
See Section 8 for information of Personal Protective Equipment.  
See Section 13 for information on disposal.

## Section 7. Handling and Storage.

**7.1.** Precautions for safe handling  
Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact.  
Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**7.2.** Conditions for safe storage, including any incompatibilities  
Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

**7.3.** Specific end use(s)  
Intended for use as Grey Zinc Primer Paint, Model Number identified in 1.1 with Description stated in 1.2.



## Section 8. Exposure Controls/Personal Protection.

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min	
1-Methoxy-2-Propanol	WEL	100 ppm(Sk)	375 mg/m <sup>3</sup> (Sk)	150 ppm(Sk)	560 mg/m <sup>3</sup> (Sk)
Acetone	WEL	500 ppm	1210 mg/m <sup>3</sup>	1500 ppm	3620 mg/m <sup>3</sup>
Butane	WEL	600 ppm	1450 mg/m <sup>3</sup>	750 ppm	1810 mg/m <sup>3</sup>
Butyl Acetate –norm	WEL	150 ppm	724 mg/m <sup>3</sup>	200 ppm	966 mg/m <sup>3</sup>
Dimethyl Ether	WEL	400 ppm	766 mg/m <sup>3</sup>	500 ppm	958 mg/m <sup>3</sup>
Propane		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating
Xylene	WEL	50 ppm(Sk)	220 mg/m <sup>3</sup> (Sk)	100 ppm(Sk)	441 mg/m <sup>3</sup> (Sk)

WEL = Workplace Exposure Limit.

### 8.2. Exposure controls

Protective equipment



#### Ventilation

Provide adequate general and local exhaust ventilation.

#### Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

#### Eye/Face Protection Eye Protection

Use approved safety goggles or face shield.

#### Skin Protection

Use solvent resisting protective gloves.

#### Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

#### Respiratory Protection

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.



## Section 9. Physical and Chemical Properties.

### 9.1. Information on basic physical and chemical properties

**The following information is not a technical specification or sales specification.**

(a) Appearance:	Aerosol.
(b) Odour:	Characteristic.
(c) Odour threshold;	No information available.
(d) pH:	No information available.
(e) Melting point/freezing point;	No information available.
(f) Initial boiling point and boiling range;	No information available.
(g) Flash point;	No information available.
(h) Evaporation rate;	No information available.
(i) Flammability (solid, gas);	No information available.
(j) Upper/lower flammability;	Lower; 0.8%    Upper; 9.0%
(k) Vapour pressure;	No information available.
(l) Vapour density;	No information available.
(m) Relative density;	No information available.
(n) Solubility (ies);	No information available.
(o) Partition coefficient: n-octanol/water;	No information available.
(p) Auto-ignition temperature;	No information available.
(q) Decomposition temperature;	No information available.
(r) Viscosity;	No information available.
(s) Explosive properties;	No information available.
(t) Oxidising properties.	No information available.



## Section 10. Stability and Reactivity.

<b>10.1.</b> Reactivity	No information available.
<b>10.2.</b> Chemical stability	Stable under normal temperature conditions.
<b>10.3.</b> Possibility of hazardous reactions	No information available.
<b>10.4.</b> Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.
<b>10.5.</b> Incompatible materials	No information available.
<b>10.6.</b> Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ).

## Section 11. Toxicological Information.

### 11.1. Information on toxicological effects

#### Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Harmful by inhalation. Irritating to respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

#### Skin contact

Harmful in contact with skin. Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. Can cause sensitization by skin contact. Irritating to skin.

#### Eye contact

Irritating to eyes. May cause chemical eye burns.

#### Route of entry

Inhalation. Skin and/or eye contact.

## Section 12. Ecological Information.

Dangerous for the environment if discharged into watercourses.

- 12.1.** Toxicity No information available.
- 12.2.** Persistence and degradability No information available.
- 12.3.** Bioaccumulative potential No information available.
- 12.4.** Mobility in soil No information available.
- 12.5.** Results of PBT and vPvB assessment No information available.
- 12.6.** Other adverse effects No information available.

## Section 13. Disposal Considerations.

### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.





**Section 14. Transport Information.**

ADR. International Carriage of Dangerous Goods by Road.

<b>14.1.</b> UN number	UN 1950	
<b>14.2.</b> Name and Description	AEROSOLS, flammable	
	Label	2.1
	Special Provisions	190 344 625
	Limited Quantities	1 L
	Excepted Quantities	E0
	Packing Instructions	P207, LP02
	Special Packaging Provisions	RR6 L2
<b>14.3.</b> Transport hazard class(es)	Class	2
	Classification Code	5F
	Transport Category	2
	Tunnel restriction code	D
<b>14.4.</b> Packing group	-	
<b>14.5.</b> Environmental hazards	Avoid release to the environment	
<b>14.6.</b> Special precautions for user	Refer to Section 2.2 Precautionary Statements	

IATA. International Air Transport Association.

<b>14.1.</b> UN number	UN 1950	
<b>14.2.</b> UN Proper Shipping Name/Description	AEROSOLS, flammable	
	Hazard Label.	Flamm. gas
	Excepted Quantity	E0
	Packaging Instructions	Passenger 203
		Ltd Qty Y203
		Cargo 203
		ERG Code 10L
	Special Provisions	A167

Special Provision A802.

Notwithstanding the absence of a packing group in column E, substances and article assigned to these entries must be packed in UN Specification packagings that meet packing group II performance standards. This does not apply when aerosols are prepared for transport in accordance with the limited quantity provisions.

<b>14.3.</b> Transport hazard class(es)	Class or Division	2.1
<b>14.4.</b> Packing group	-	
<b>14.5.</b> Environmental hazards	Avoid release to the environment	
<b>14.6.</b> Special precautions for user	Refer to Section 2.2 Precautionary Statements	

IMDG. International Maritime Dangerous Goods.

<b>14.1.</b> UN number	UN 1950	
<b>14.2.</b> UN proper shipping name	AEROSOLS, flammable	
	Special Provisions	63, 190 277, 327, 344, 959
	Limited Quantities	See Special Provision 277
	Excepted Quantities	E0
	Packaging Instructions	P207, LP02
	Packaging Provisions	PP87, L2
<b>14.3.</b> Transport hazard class(es)	Class or Division	2
	Subsidiary Risk(s)	See Special Provision 63
<b>14.4.</b> Packing group	-	
<b>14.5.</b> Environmental hazards	Avoid release to the environment	
<b>14.6.</b> Special precautions for user	Refer to Section 2.2 Precautionary Statements	
<b>14.7.</b> Transport in bulk – Maritime only.	Bulk transport is not applicable to this product	



## Section 15. Regulatory Information.

**15.1.** Safety, health and environmental regulations/legislation specific for the substance or mixture  
No information available.

**15.2.** Chemical safety assessment  
No information available.

## Section 16. Additional Information.

Full text of Phrases and Statements used in Section 3;

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation
- H336 May cause drowsiness of dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

The above information is believed to be accurate and represents the best information currently available.

No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	04/03/16	First issue.
2	15/09/16	Sections 3.2, 14 & 15.

End of Safety Data Sheet.