



Loosen pressed connections such as crankshafts and fastening materials (screws, bolts and nuts) with MOTIP Freezer. MOTIP Freezer briefly decreases temperature to -50°C to loosen pressed connections and has a precise jet spray.

Ord.-no: 090306

Quality & properties

Briefly decreases the temperature to -50°C
Very effective
Directed jetspray
360° valve

Physical & chemical data

Base: Propane / butane
Colourname: no colour
Smell: Characteristic
Surfaces: Crankshafts, Fasteners (screws, bolts and nuts)
Minimum Working Temperature: 10°C
Maximum Working Temperature: 25°C
Flash point: n.a.
Storage stability: 10 years
Content: 500 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.
The aerosol should have room temperature.
Best processing temperature 10 to 25°C .
Before use, shake the aerosol.
Spray the connection to be treated by repeatedly, briefly pressing the nozzle.
As a result of the fierce decrease in temperature, the connection can be loosed.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.