

## 1. Identification of the substance/mixture and of the company/undertaking

# 1.1 Product identifier

SILVERHOOK Petrol Injector Cleaner

**1.2 Relevant identified uses of the substance or mixture and uses advised against** Fuel Additive

# **1.3** Details of the supplier of the safety data sheet

Supplier

Silverhook Ltd Unit 14, Bates Road Harold Wood London RM3 0JH England

# **1.4 Emergency Telephone Number**

+44 (0)1708330500 (available during office hours 8:00 - 16:30)

### 2. Hazards identification

# 2.1 Classification of the substance or mixture

# Classification according to Directive 67/548/EEC or 1999/45/EC

Harmful: may cause lung damage if swallowed. Xn ; R 65  $\,$   $\,$  R 66  $\,$ 

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

# 2.2 Label elements

# Labelling (67/548/EEC or 1999/45/EC)

Hazard symbols and hazard statements of dangerous substances and preparations



S-phrases

**R-phrases** 65 66

Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. This material and its container must be disposed of in a safe way. Avoid contact with skin.

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms



Health hazard (GHS08) May be fatal if swallowed and enters airways. Signal word Danger Hazard Statements Precautionary statements

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not induce vomiting.



		d exposure may cause skin dryness or cracking.	
	Other hazards None		
	Composition/ Information of	n ingredients	
<u>)</u>	Mixtures Hazardous ingredients		
	DISTILLATES (PETROLEUM), HYDROTR	EATED LIGHT / KEROSINE - UNSPECIFIED ; EC No : 265-149-8; CAS No. : 64742-47-8	
	Weight fraction : Classification 67/548/EEC : Classification 1272/2008 [CLP] :	50 - 100 % Xn ; R65 Asp.Tox. 1 ; H304	
	HYDROCARBONS,C10-13,n-ALKANES, <2% AROMATIC; REACH registration No: n/a ; EC No : 918-481-9; CAS No. :		
	Weight fraction : Classification 67/548/EEC : Classification 1272/2008 [CLP] :	2 - 3 % Xn ; R65 R66 Asp.Tox. 1 ; H304	
	, , ,	LYISOBUTYLENE DERIVIATIVES EC No POLYMER	
	Weight fraction : Classification 67/548/EEC : Classification 1272/2008 [CLP] :	1.5 – 3 % Xn ; R52/53 Aquatic Chronic 3 ; H412	
	HYDROCARBONS, C10, AROMATICS; EC No : 919-284-0-8		
	Weight fraction : Classification 67/548/EEC : Classification 1272/2008 [CLP] : Additional information Full text of R-, H- and EUH-phrases: see	< 1 % N ; R51/53 Xn ; R65 R67 R66 Asp.Tox. 1 ; H304 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411 e section 16.	
. First-aid measures			
4.1	Description of first aid measures General information Medical treatment necessary. After inhalation No special measures are necessary.		
	In case of skin contact After cleaning apply high-fat content skin care cream.		
	After eye contact No special measures are necessary.		
	<b>After ingestion</b> Rinse mouth thoroughly with water. Give nothing to eat or drink. Do not induce vomiting. Call a physician in any case!		
	-	live nothing to eat or drink. Do not induce vomiting. Call a physician in any case!	
2	Rinse mouth thoroughly with water.	nd effects, both acute and delayed	
2	Rinse mouth thoroughly with water. C Most important symptoms an Allergic reactions Respiratory complaint	nd effects, both acute and delayed ts. medical attention and special treatment needed	

Page : 2 / 7



	Strong water jet.		
5.2	Special hazards arising from the substance or mixture		
	Hazardous combustion products		
	In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide. Nitrogen oxides (NOx)		
5.3	Advice for firefighters		
	Do not inhale explosion and combustion gases. Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses.		
	Special protective equipment for firefighters		
	Wear a self-contained breathing apparatus and chemical protective clothing.		
6.	Accidental release measures		
6.1	Personal precautions, protective equipment and emergency procedures		
6.1	<b>Personal precautions, protective equipment and emergency procedures</b> Special danger of slipping by leaking/spilling product. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Remove persons to safety. See protective measures under point 7 and 8.		
6.1 6.2	Special danger of slipping by leaking/spilling product. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Remove		
	Special danger of slipping by leaking/spilling product. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Remove persons to safety. See protective measures under point 7 and 8.		
	Special danger of slipping by leaking/spilling product. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Remove persons to safety. See protective measures under point 7 and 8. <b>Environmental precautions</b> Ensure all waste water is collected and treated via a waste water treatment plant. In case of gas escape or of entry into waterways, soil or		
6.2	Special danger of slipping by leaking/spilling product. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Remove persons to safety. See protective measures under point 7 and 8. <b>Environmental precautions</b> Ensure all waste water is collected and treated via a waste water treatment plant. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.		
6.2	Special danger of slipping by leaking/spilling product. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Remove persons to safety. See protective measures under point 7 and 8. Environmental precautions Ensure all waste water is collected and treated via a waste water treatment plant. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Methods and material for containment and cleaning up		
6.2 6.3	Special danger of slipping by leaking/spilling product. Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Remove persons to safety. See protective measures under point 7 and 8.  Environmental precautions Ensure all waste water is collected and treated via a waste water treatment plant. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.  Methods and material for containment and cleaning up Suitable material for taking up: Sand. Kieselguhr. Universal binder Sawdust. Collect in closed and suitable containers for disposal.		

# 7. Handling and storage

#### 7.1 Precautions for safe handling

Unsuitable extinguishing media

Provide adequate ventilation as well as local exhaustion at critical locations. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. All work processes must always be designed so that the following is as low as possible: Eye contact. Skin contact Inhalation of vapours or spray/mists In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Wear personal protection equipment. (see chapter 8).

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Never use pressure to empty container.

#### Hints on storage assembly

Keep away from: Oxidising agent Acid. Alkali Storage class : 10

# 7.3 Specific end uses

None

#### 8. Exposure controls / Personal protection

#### 8.1 Control parameters

None

# 8.2 Exposure controls

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

#### Personal protective equipment

Eye / face protection

Eye glasses with side protection

# Skin protection





#### Hand protection

Gloves with long cuffs The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. Breakthrough times and swelling properties of the material must be taken into consideration.

#### **Body protection**

Overall.

#### **Respiratory protection**

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation. insufficient exhaust Handling larger quantities. Container device with compressed air (DIN EN 137). / Filtering device (full mask or mouthpiece) with filter: Filter types:A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m3 (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 1000 mL/m3 (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 1000 mL/m3 (0.1 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 1000 mL/m3 (0.5 % by vol.); class 3: maximum permitted contaminant concentration in inhaled air = 1000 mL/m3 (1.0 % by vol.)

#### **Environmental exposure controls**

Send to a hazardous waste incinerator facility under observation of official regulations.

#### 9. Physical and chemical properties

#### <sup>9.1</sup> Information on basic physical and chemical properties Safety relevant basis data

Physical state :	Liquid			
Odour :	Characteristic Hydrocarbon			
Colour :	Light Brown			
Boiling temperature / boiling range@ 760mmHg/°C :	200 - 250			
Flash point (PMcc)/°C :	> 75			
Vapour pressure@50°C	< 1000 hPa			
Density @15°C/ g/cm <sup>3</sup> :	0.80			
Water solubility @20°C:	Insoluble			
Viscosity@ 40°C / mm2/s :	< 7.5			
Other information				
pH value	N/A			
Ethanol content %	0			

# 10. Stability and reactivity

#### 10.1 Reactivity

9.2

No information available.

# 10.2 Chemical stability

No information available.

#### **10.3 Possibility of hazardous reactions** No information available.

**10.4 Conditions to avoid** No information available.

### **10.5** Incompatible materials

Exothermic reaction with: Oxidising agent. Strong acid Strong alkali

### **10.6 Hazardous decomposition products**

Decomposition with: Carbon dioxide (CO2). Carbon monoxide. Nitrogen oxides (NOx).

## 11. Toxicological information

This mixture is classified as dangerous according to 1999/45/EC. This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP]. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

#### **11.1 Information on toxicological effects**

Harmful: may cause lung damage if swallowed. For viscosity data, see chapter 9. Repeated exposure may cause skin dryness or cracking. Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc.

# Acute effects

Acute oral toxicity Parameter :

LD50 ( ALKANES, C10-14-ISO- ; EC No : 918-481-9)



Exposure route :	Oral
Effective dose :	> 10000 mg/kg
Acute dermal toxicity	
Parameter :	LD50 ( ALKANES, C10-13-ISO- ; EC No : 918-481-9)
Exposure route :	Dermal
Effective dose :	> 3160 mg/kg
Acute inhalation toxicity	
Parameter :	LC50 ( SOLVENT NAPHTA (PETROLEUM), HEAVY AROMATIC ; CAS No. : 64742-94-5 )
Exposure route :	Inhalation
Species :	Rat
Effective dose :	> 590 mg/m <sup>3</sup>
Exposure time :	4 h
Ecological information	

# 12. Ecological information

# 12.1 Toxicity

Α

### **Aquatic toxicity**

Harmless to aquatic organisms up to the tested concentration

cute (short-term) algae toxicity	
Parameter :	EC50 (SOLVENT NAPHTA (PETROLEUM), HEAVY AROMATIC ; CAS No. : 64742-94-5 )
Species :	Algae
Effective dose :	1 - 3 mg/l
Exposure time :	72 h
Parameter :	EC50 (SOLVENT NAPHTA (PETROLEUM), HEAVY AROMATIC ; CAS No. : 64742-94-5 )
Species :	Daphnia
Effective dose :	3 - 10 mg/l
Exposure time :	48 h

#### 12.2 Persistence and degradability

No information available.

### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

# 12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII

## 12.6 Other adverse effects

The evaluation was carried out according to the calculation method of the preparation directive.

# 12.7 Further ecological information

None

## **13.** Disposal considerations

### 13.1 Waste treatment methods

Send to a hazardous waste incinerator facility under observation of official regulations. Clean IBCs or drums at approved facility only. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of. Handle contaminated packages in the same way as the substance itself.

# 14. Transport information

#### 14.1 UN number

No dangerous good in sense of this transport regulation.

- 14.2 UN proper shipping name No dangerous good in sense of this transport regulation.
   14.3 Transport barrand class(cor)
- 14.3 Transport hazard class(es) Land transport (ADR/RID)



Not subject to ADR/RID. Class(es) : -Sea transport (IMDG) Not subject to IMDG code. Class(es) : -Air transport (ICAO-TI / IATA-DGR) Not subject to IATA regulations. Class(es) : -14.4 Packing group No dangerous good in sense of this transport regulation.

# **14.5** Environmental hazards No dangerous good in sense of this transport regulation.

# 14.6 Special precautions for user

None

### 15. Regulatory information

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture National regulations

Technische Anleitung Luft (TA-Luft)Weight fraction (Number 5.2.5. I) : < 5 %</td>Water hazard class (WGK)

Class: 2 (Hazardous to water) Classification according to VwVwS

### 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **16.** Other information

#### 16.1 Indication of changes

03. Hazardous ingredients

### **16.2** Abbreviations and acronyms

None

#### 16.3 Key literature references and sources for data None

### 16.5 Relevant R-, H- and EUH-phrases (Number and full text)

H304	May be fatal if swallowed and enters
H336	airways. May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated
H411	exposure. Toxic to aquatic life with long lasting effects.
H412	May cause long lasting harmful effects to aquatic life.
H413	Harmful to aquatic life with long lasting effect
48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
53	May cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

### 16.6 Training advice

None

### **16.7** Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is



intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.