# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name: LIBERON - STONE FLOOR CLEANER - 5 L

Product code: 126766

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaner

## Use descriptor system (REACH):

Paints, varnishes and related products coating with layered application.

#### 1.3. Details of the supplier of the safety data sheet

Registered company name: LIBERON Ltd

Address: .Mountfield Industrial Estate KENT TN28 8XU NEW ROMNEY GB Telephone: + (44) 1797 367 555. Fax: + (44) 1797 367 575. Telex: .

fds.produits@v33.com www.liberon.co.uk

## 1.4. Emergency telephone number: .

Association/Organisation: .

#### Other emergency numbers

UK/NI: 111 - Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

Republic of Ireland: +353 (0)1 809

2166 - Emergency medical information: 8am-10pm (seven days) contact NPIC, Beaumont Hospital, Dublin 9 DOV2NO, Ireland.

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Skin corrosion, Category 1A (Skin Corr. 1A, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

# 2.2. Label elements

## In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

Signal Word : DANGER

Product identifiers:

EC 229-912-9 DISODIUM METASILICATE

Additional labeling :

EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

EUH208 Contains REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H

-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

Hazard statements:

H314 Causes severe skin burns and eye damage.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

LIBERON - STONE FLOOR CLEANER - 5 L - 126766

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/

...

Precautionary statements - Response :

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...

Precautionary statements - Disposal:

P501 Dispose of contents/container to a waste collection center (contact the local authority)

(EQ) 1070/0000

## 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006. The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

#### Composition:

Identification	(EC) 1272/2008	Note	%
INDEX: 014_010_00_8	GHS05, GHS07		2.5 <= x % < 10
CAS: 6834-92-0	Dgr		
EC: 229-912-9	Met. Corr. 1, H290		
REACH: 01-2119449811-37	Skin Corr. 1B, H314		
	STOT SE 3, H335		
DISODIUM METASILICATE			
INDEX: Z895	GHS07, GHS05		2.5 <= x % < 10
CAS: 90583-18-9	Dgr		
EC: 292-216-9	Acute Tox. 4, H302		
REACH: 01-2119970645-28	Skin Irrit. 2, H315		
	Eye Dam. 1, H318		
ACIDE SULFURIQUE, ESTERS DE	Aquatic Chronic 3, H412		
MONO-ALKYLES EN C12-14,	·		
COMPOSÉS AVEC LA			
TRIÉTHANOLAMINE			
INDEX: 603 064 00 3	GHS07, GHS02	[1]	2.5 <= x % < 10
CAS: 107-98-2	Wng	-	
EC: 203-539-1	Flam. Liq. 3, H226		
REACH: 01-2119457435-35	STOT SE 3, H336		
	,		
MONOPROPYLENE GLYCOL METHYL			
ETHER			
INDEX: 613_088_006B	GHS06, GHS05, GHS09		0 <= x % < 0.05
CAS: 2634-33-5	Dgr		
EC: 220-120-9	Acute Tox. 4, H302		
	Skin Irrit. 2, H315		
1,2-BENZISOTHIAZOL-3(2H)-ONE	Skin Sens. 1, H317		
. ,	Eye Dam. 1, H318		
	Acute Tox. 2, H330		
	Aquatic Chronic 2, H411		
	Aquatic Acute 1, H400		
	M Acute = 1		
INDEX: Z117	GHS06, GHS05, GHS09		0 <= x % < 0.0015
CAS: 55965-84-9	Dgr		
REACH: 01-2120764691-48	Acute Tox. 3, H301		
	Acute Tox. 2, H310		
REACTION MASS OF:	Skin Corr. 1C, H314		
5-CHLORO-2-METHYL-4-ISOTHIAZOLI	Skin Sens. 1A, H317		

N-3-ONE AND 2-METHYL-2H	Eye Dam. 1, H318		
-ISOTHIAZOL-3-ONE (3:1)	Acute Tox. 2, H330		
	Aquatic Acute 1, H400		
	M Acute = 100		
	Aquatic Chronic 1, H410		
	M Chronic = 100		

# Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: Z895	Eye Dam. 1: H318 C>= 20%	
CAS: 90583-18-9	Eye Irrit. 2: H319 10% <= C < 20%	
EC: 292-216-9		
REACH: 01-2119970645-28		
ACIDE SULFURIQUE, ESTERS DE		
MONO-ALKYLES EN C12-14,		
COMPOSÉS AVEC LA		
TRIÉTHANOLAMINE		
INDEX: 603_064_00_3		inhalation: ATE = 27.596 mg/l
CAS: 107-98-2		4h
EC: 203-539-1		(vapours)
REACH: 01-2119457435-35		oral: ATE = 4016 mg/kg BW
MONOPROPYLENE GLYCOL METHYL		
ETHER		
INDEX: 613_088_006B	Skin Sens. 1: H317 C>= 0.05%	
CAS: 2634-33-5		
EC: 220-120-9		
1,2-BENZISOTHIAZOL-3(2H)-ONE		
INDEX: Z117	Eye Dam. 1: H318 C>= 0.25%	
CAS: 55965-84-9	Eye Irrit. 2: H319 0.025% <= C <	
REACH: 01-2120764691-48	0.25%	
	Skin Sens. 1A: H317 C>= 0.0015%	
REACTION MASS OF:		
5-CHLORO-2-METHYL-4-ISOTHIAZOLI		
N-3-ONE AND 2-METHYL-2H		
-ISOTHIAZOL-3-ONE (3:1)		

## Information on ingredients:

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

#### **SECTION 4: FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### 4.1. description of first aid measures

# In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

#### In the event of splashes or contact with skin:

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

#### In the event of swallowing:

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

## 4.2. Most important symptoms and effects, both acute and delayed

No data available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## **SECTION 5: FIREFIGHTING MEASURES**

Non-flammable.

#### 5.1. Extinguishing media

#### Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

#### Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

#### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

#### 5.3. Advice for firefighters

No data available.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

## For non first aid worker

Avoid any contact with the skin and eyes.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

## 6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

# 6.4. Reference to other sections

No data available.

# **SECTION 7: HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

#### Fire prevention:

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

## Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

#### Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

#### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Do not allow to freeze

#### **Packaging**

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

#### Occupational exposure limits:

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE):

CAS	VME-mg/m3:	VME-ppm:	VLE-mg/m3:	VLE-ppm:	Notes :
107-98-2	375	100	568	150	Peau

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME :	VME :	Excess	Notes	
107-98-2		100 ppm		2(1)	
		370 mg/m³			

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021):

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes :	TMP No :
107-98-2	50	188	100	375	*	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020):

CAS	TWA:	STEL:	Ceiling :	Definition :	Criteria :	
107-98-2	100 ppm	150 ppm		Sk		
	375 ma/m³	560 mg/m³				

#### Derived no effect level (DNEL) or derived minimum effect level (DMEL):

MONOPROPYLENE GLYCOL METHYL ETHER (CAS: 107-98-2)

Final use: Workers.

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 50.6 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Short term local effects.

DNEL: 553.5 mg of substance/m3

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 369 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects:

DNEL:

Long term systemic effects.

3.3 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 18.1 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 43.9 mg of substance/m3

ACIDE SULFURIQUE, ESTERS DE MONO-ALKYLES EN C12-14, COMPOSÉS AVEC LA TRIÉTHANOLAMINE (CAS: 90583-18-9)

Final use: Workers.

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 4060 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 285 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects:

DNEL:

Long term systemic effects.

24 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 2440 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 85 mg of substance/m3

# Predicted no effect concentration (PNEC):

MONOPROPYLENE GLYCOL METHYL ETHER (CAS: 107-98-2)
Environmental compartment: Soil.
PNEC: 2.47 mg/kg

Environmental compartment: Fresh water.

PNEC: 10 mg/l

Environmental compartment: Sea water. PNEC: 100 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 41.6 mg/kg

Environmental compartment: Marine sediment. PNEC: 4.17 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 100 mg/l

ACIDE SULFURIQUE, ESTERS DE MONO-ALKYLES EN C12-14, COMPOSÉS AVEC LA TRIÉTHANOLAMINE (CAS: 90583-18-9)

Environmental compartment: Soil.
PNEC: 0.083 mg/kg

Environmental compartment: Fresh water. PNEC: 0.012 mg/l

Environmental compartment: Sea water. PNEC: 0.0012 mg/l

Environmental compartment: Intermittent waste water.

PNEC: 0.036 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 0.422 mg/kg

Environmental compartment: Marine sediment.

PNEC: 0.0422 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 1.35 mg/l

## 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact. Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Suitable type of protective boots:

In the event of minor spatter, wear protective boots or half-boots against chemical risks in accordance with standard EN13832-2.

In the event of prolonged contact, wear boots or half-boots with liquid-chemical-resistant and waterproof soles and uppers in accordance with standard EN13832-3.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties

# Physical state

Physical state :	Fluid liquid.
Colour	
Unspecified	
Odour	
Odour threshold :	Not stated.
Melting point	
Melting point/melting range :	Not relevant.
Freezing point	
Freezing point / Freezing range :	Not stated.
Boiling point or initial boiling point and boiling ran	nge
Boiling point/boiling range :	Not relevant.

## **Flammability**

· ··································	
Flammability (solid, gas) :	Not stated.
Lower and upper explosion limit	
Explosive properties, lower explosivity limit (%):	Not stated.
Explosive properties, upper explosivity limit (%):	Not stated.
Flash point	
Flash point interval :	Not relevant.
Auto-ignition temperature	
Self-ignition temperature :	Not relevant.
Decomposition temperature	·
Decomposition point/decomposition range :	Not relevant.
pH	
pH (aqueous solution) :	Not stated.
pH:	12.50 .
	Strongly basic.
Kinematic viscosity	
Viscosity:	Not stated.
Solubility	
Water solubility:	Dilutable.
Fat solubility :	Not stated.
Partition coefficient n-octanol/water (log value)	
Partition coefficient: n-octanol/water :	Not stated.
Vapour pressure	
Vapour pressure (50°C) :	Not relevant.
Density and/or relative density	
Density:	1-1.05
Relative vapour density	'
Vapour density :	Not stated.

#### 9.2. Other information

No data available.

## 9.2.1. Information with regard to physical hazard classes

No data available.

# 9.2.2. Other safety characteristics

No data available.

# **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### 10.4. Conditions to avoid

Avoid:

- frost

## 10.5. Incompatible materials

No data available

## 10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three

minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

#### 11.1.1. Substances

#### Acute toxicity:

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Oral route : LD50 > 2000 mg/kg

Dermal route: LD50 > 5000 mg/kg

MONOPROPYLENE GLYCOL METHYL ETHER (CAS: 107-98-2)

Oral route : LD50 = 4016 mg/kg

Species: Rat

Dermal route: LD50 > 2000 mg/kg

Species: Rabbit

Inhalation route (Vapours): LC50 = 27.596 mg/l

Species: Rat

Duration of exposure: 4 h

ACIDE SULFURIQUE, ESTERS DE MONO-ALKYLES EN C12-14, COMPOSÉS AVEC LA TRIÉTHANOLAMINE (CAS: 90583-18-9)

Oral route : LD50 > 5000 mg/kg

#### Skin corrosion/skin irritation:

ACIDE SULFURIQUE, ESTERS DE MONO-ALKYLES EN C12-14, COMPOSÉS AVEC LA TRIÉTHANOLAMINE (CAS: 90583-18-9)

Irritation : Causes skin irritation.

2.3 <= Average score <= 4.0

Species: Rabbit

OCDE Ligne directrice 404 (Effet irritant/corrosif aigu sur la peau.)

#### 11.1.2. Mixture

#### Skin corrosion/skin irritation:

Corrosive classification is based on an extreme pH value.

# Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

#### 11.2. Information on other hazards

# Monograph(s) from the IARC (International Agency for Research on Cancer):

CAS 123-35-3: IARC Group 2B: The agent is possibly carcinogenic to humans.

CAS 5989-27-5: IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

## **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1. Toxicity

#### 12.1.1. Substances

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Fish toxicity: LC50 = 0.22 mg/l

Factor M = 1

Species : Oncorhynchus mykiss Duration of exposure : 96 h

OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity: EC50 = 0.1 mg/l

Factor M = 10

Species : Daphnia magna Duration of exposure : 48 h

OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity: ECr50 = 0.0052 mg/l

Factor M = 100

Species : Skeletonema costatum

Duration of exposure: 48 h

OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)

EC50 mg/l Factor M = 10

Species : Skeletonema costatum Duration of exposure : 48 h

ISO 10253 (Essai d'inhibition de la croissance des algues marines avec

Skeletonema costatum et Phaeodactylum tricornutum)

NOEC = 0.00064 mg/lFactor M = 100

Species : Skeletonema costatum Duration of exposure : 48 h

ISO 10253 (Essai d'inhibition de la croissance des algues marines avec

Skeletonema costatum et Phaeodactylum tricornutum)

MONOPROPYLENE GLYCOL METHYL ETHER (CAS: 107-98-2)

Fish toxicity: LC50 >= 1000 mg/l

Species : Oncorhynchus mykiss Duration of exposure : 96 h

Crustacean toxicity: EC50 = 23300 mg/l

Species : Daphnia magna Duration of exposure : 48 h

Algae toxicity: ECr50 > 1000 mg/l

Species: Pseudokirchnerella subcapitata

ACIDE SULFURIQUE, ESTERS DE MONO-ALKYLES EN C12-14, COMPOSÉS AVEC LA TRIÉTHANOLAMINE (CAS: 90583-18-9)

Fish toxicity: 1 < LC50 <= 10 mg/l

Species: Oncorhynchus mykiss

ISO 7346-2 (Détermination de la toxicité aiguë létale de substances vis-à-vis d'un poisson d'eau douce [Brachydanio rerio Hamilton-Buchanan

(Teleostei, Cyprinidae)] - Partie 2: Méthode semi-statique)

NOEC > 1 mg/l

Species: Pimephales promelas

Crustacean toxicity: 10 < EC50 <= 100 mg/l

Species : Daphnia magna Duration of exposure : 48 h Autres lignes directrices

0,1 < NOEC <= 1 mg/l Species : Daphnia magna

Algae toxicity: 10 < ECr50 <= 100 mg/l

Species: Scenedesmus subspicatus

Duration of exposure: 72 h

Méthode REACH C.3 (Essai d'inhibition des algues)

NOEC > 1 mg/l

Species : Scenedesmus subspicatus

Méthode REACH C.3 (Essai d'inhibition des algues)

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

# 12.2. Persistence and degradability

## 12.2.1. Substances

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Biodegradability: no degradability data is available, the substance is considered as not

degrading quickly.

1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)

Biodegradability: Rapidly degradable.

MONOPROPYLENE GLYCOL METHYL ETHER (CAS: 107-98-2)

Biodegradability: Rapidly degradable.

ACIDE SULFURIQUE, ESTERS DE MONO-ALKYLES EN C12-14, COMPOSÉS AVEC LA TRIÉTHANOLAMINE (CAS: 90583-18-9)

Biodegradability: Rapidly degradable.

#### 12.3. Bioaccumulative potential

#### 12.3.1. Substances

REACTION MASS OF: 5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE AND 2-METHYL-2H -ISOTHIAZOL-3-ONE (3:1) (CAS: 55965-84-9)

Octanol/water partition coefficient : log Koe <= 0.71

OCDE Ligne directrice 117 (Coefficient de partage (n-octanol/eau), méthode

HPLC)

Bioaccumulation: BCF = 3.16

MONOPROPYLENE GLYCOL METHYL ETHER (CAS: 107-98-2)
Octanol/water partition coefficient: log Koe < 3.

Bioaccumulation: BCF < 100

ACIDE SULFURIQUE, ESTERS DE MONO-ALKYLES EN C12-14, COMPOSÉS AVEC LA TRIÉTHANOLAMINE (CAS: 90583-18-9)

Octanol/water partition coefficient : log Koe < -0.866

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

No data available.

# 12.6. Endocrine disrupting properties

No data available.

#### 12.7. Other adverse effects

No data available.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### 13.1. Waste treatment methods

Do not pour into drains or waterways.

## Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

# Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

# **SECTION 14: TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

# 14.1. UN number or ID number

3266

# 14.2. UN proper shipping name

 ${\tt UN3266=CORROSIVE\;LIQUID,\;BASIC,\;INORGANIC,\;N.O.S.}$ 

(disodium metasilicate)

# 14.3. Transport hazard class(es)

- Classification:



3

## 14.4. Packing group

Ш

#### 14.5. Environmental hazards

•

#### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel	
	8	C5	III	8	80	5 L	274	E1	3	E	
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregati on		'
	8	-	III	5 L	F-A. S-B	223 274	E1	Category A SW2	SGG18 SG35		
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ		
	8	-	III	852	5 L	856	60 L	A3 A803	E1		
	8	-	III	Y841	1 L	-	-	A3 A803	E1		

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

#### - Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

#### - Particular provisions :

No data available.

# 15.2. Chemical safety assessment

This product contains at least one substance with exposure scenarios. The RMM (risk management measures) and OC (Operating conditions) are included in the body of the SDS.

# **SECTION 16: OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

# Wording of the phrases mentioned in section ${\bf 3}$ :

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)	Version 3.1 (12-08-2022) - Page 13/13
LIBERON - STONE FLOOR CLEANER - 5 L - 126766	

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Abbreviations:

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50: The concentration of a test substance resulting in 50% lethality in a given period.

 $\ensuremath{\mathsf{EC50}}$  : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC: The concentration with no observed effect.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE: Acute Toxicity Estimate

BW: Body Weight

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

STEL: Short-term exposure limit
TWA: Time Weighted Averages
TMP: French Occupational Illness table
TLV: Threshold Limit Value (exposure)

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS05: Corrosion

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.